

Refit Solutions from GE



Application illustration only, subject lamps not used in photo.

Type C LED Tubes - 8' Glass

Convert your existing linear fluorescent fixture to LED lighting without needing a comprehensive reinstall. LED tubes are ideal for those seeking high energy savings with minimal installation time. Each LED tube is operated by a GE Lightech™ driver. See reverse for LED tubes and Lightech driver product details.

FEATURES

- 8' glass tubes
- 4,200-4,400 lumen option available
- >120 total system lumens per watt (LPW)
- 3000K, 3500K, 4000K and 5000K color temperatures
- 50,000-hour rated life
- UL & CUL Classified
 - in compliance with UL 1598 certification
- Open or Enclosed Fixtures
- Damp rating
- 5 year warranty

BENEFITS

- Fast and easy LED upgrade
- Low energy LFL replacement
- 66% longer life than LFL (50,000 vs. 30,000 hours)
- Better quality of light – instant on
- Fully illuminates fixture
 - 270° light distribution
- Easy disposal, non-hazardous waste
- State-of-Art USA Assembly
 - Perfect for special projects

To learn more about saving money and energy, go to: www.led.com

Information provided is subject to change without notice. Please verify all details with GE. All values are design or typical values when measured under laboratory conditions, and GE makes no warranty or guarantee, expressed or implied, that such performance will be obtained under end-use conditions.

Product Specifications - Type C 8 Foot LED Glass Tubes



Refit LED Tubes

GE Product Code	Description	Bulb Shape	Base	Watts	Case Quantity	Length (in)	Initial Lumens	Color Temp (K°)	CRI	*Rated Life L70 (Hrs)
8ft LED Tubes										
62326	LED36T8/G/8/830	T8	Single Pin (Fa8)	30	20	96"	4200	3000	80+	50,000
62327	LED36T8/G/8/835	T8	Single Pin (Fa8)	30	20	96"	4400	3500	80+	50,000
62329	LED36T8/G/8/840	T8	Single Pin (Fa8)	30	20	96"	4400	4000	80+	50,000
62349	LED36T8/G/8/850	T8	Single Pin (Fa8)	30	20	96"	4400	5000	80+	50,000

Ligtech Drivers™ - Non-Dimming

GE Product Code	Description	# of Lamps
38970	LED15T8/DR/UN/2L	2
94384	LED21T8/DR/1L	1
94385	LED21T8/DR/2L	2

Ligtech Drivers - Dimming

GE Product Code	Description	# of Lamps
38974	LED15T8/DR/D2L	2
38975	LED15T8/DR/4DL	4
60041	LED21T8/DR/D/2L	2
34016	LED21T8/DR/VLC/2L	2
62030	LED21T8/DR/D/4L	4
63126	LED36T8/DR/D2L	2

General Characteristics - Non Dimming

GE Product Code	38970	94384	94385
Output Current (A)	0.44*2	0.62	0.62*2
Input Wattage (Max)	30	21	42
Input Voltage (V)		120-277V	
Input Frequency (Hz)		50/60Hz	
Efficiency (%)		> .9%	
Output Type		DC	
Output Voltage Range		27-33V	
Dimmability		None	
Ambient Temp Min		-4°F	
Ambient Temp Max		104°F	
Case Temperature		158°F	

General Characteristics - Dimming

GE Product Code	38974	38975	60041	34016	62030	63126
Output Current (A)	0.44*2	0.44*4	0.62*2	0.62*2	0.62*4	0.54*2
Input Wattage (Max)	30	60	42	42	84	72 (36 x 2)
Input Voltage (V)			120-277V			120-277V
Input Frequency (Hz)			50/60Hz			50/60Hz
Efficiency (%)			> .9%			> .9%
Output Type			DC			DC
Output Voltage Range			27-33V			26-34V
Dimmability			0-10V			0-10V
Ambient Temp Min			-4°F			-4°F
Ambient Temp Max			104°F			113°F
Case Temperature			158°F			158°F

Dimensions - Non Dimming

GE Product Code	38970	94384	94385
Weight	1.01	1.01	1.08
Casing Length (in)		9.5	
Casing Width (in)		1.3	
Casing Height (in)		1	
Lead Exit Length (in)		26	
Input Wire Length (in)		36	
Output Wire Length (in)		38	

Dimensions - Dimming

GE Product Code	38974	38975	60041	34016	62030	63126
Weight			1.01		1.08	1.01
Casing Length (in)			9.5		9.5	9.5
Casing Width (in)			1.3		1.7	1.3
Casing Height (in)			1		1	1
Lead Exit Length (in)			26		26	26
Input Wire Length (in)			36		36	36
Output Wire Length (in)			38		42	38



Product is compliant with material restriction requirements of RoHS



www.led.com

GE and the GE Monogram are trademarks of the General Electric Company and are used under license. All other trademarks are the property of their respective owners. Information provided is subject to change without notice. All values are design or typical values when measured under laboratory conditions. GE Lighting and GE Lighting Solutions, LLC are businesses of the General Electric Company. © 2019 Current, powered by GE.

LEDL035 (Rev 07/11/19)