

Refit Solutions



Application illustration only, subject lamps not used in photo.

Type A Integrated LED Tubes-Glass – Assembled in USA

Convert your existing linear fluorescent fixture to LED lighting without needing a comprehensive reinstall. LED tubes are ideal for those seeking high energy savings with minimal installation time. Each LED tube is assembled in USA and outfitted with an internal GE driver. The GE integrated LED tubes run on electronic T8 instant-start or programmed start ballast.

FEATURES

- 4' glass tube
- 1,900 – 2,000 lumen options available
- > 120 total system lumens per watt (LPW)
- 3000K, 3500K, 4000K and 5000K color temperature
- 50,000-hour rated life
- Open or enclosed fixtures
- 5 year warranty
- UL and CUL- approved technologies
–in compliance with UL 1598 certification

BENEFITS

- Fast and Easy LED upgrade
- Low energy LFL replacement
- 66% longer life than LFL (50,000 vs. 30,000 hours)
- Better quality of light
–instant on
- Fully illuminates fixture
>270° light distribution
- Easy disposal, non-hazardous waste

To learn more about saving money and energy, go to www.led.com.

Product Specifications

Integrated Refit LED Tubes



GE Product Code	Description	Bulb Shape	Base	Low BF Watts	Normal BF Watts	High BF Watts	Case Qty	Length (in)	Low BF Initial Lumens	Normal BF Initial Lumens	High BF Initial Lumens	Color Temp (°K)	CRI	Rated Life (L70)	DLC Listed
4ft LED Tube															
21309	LED13ET8G4/830US	T8	Med Bi-Pin(G13)	12	13.5	19.5	20	48"	1750	1900	2600	3000	80	50,000	-
21344	LED13ET8G4/835US	T8	Med Bi-Pin (G13)	12	13.5	19.5	20	48"	1800	2000	2650	3500	80	50,000	-
21373	LED13ET8G4/840US	T8	Med Bi-Pin(G13)	12	13.5	19.5	20	48"	1800	2000	2650	4000	80	50,000	-
21377	LED13ET8G4/850US	T8	Med Bi-Pin(G13)	12	13.5	19.5	20	48"	1800	2000	2650	5000	80	50,000	-



Product is compliant with material restriction requirements of RoHS

current
powered by GE

www.led.com

GE and the GE Monogram are trademarks of the General Electric Company and are used under license. Information provided is subject to change without notice. All values are design or typical values when measured under laboratory conditions, and GE makes no warranty or guarantee, express or implied, that such performance will be obtained under end-use conditions. © 2019 Current, powered by GE

LEDL054 (Rev 08/01/19)